Ming Feng Lighting Co.,Ltd

Tel:+86-769-2203-6051 Fax: +86-769-2203-6052

Add: Wen Tang Administration, East City, Dongguan, Guangdong Province, China.

## MF-GPC03 Spec

## **FEATURES** Light Source: CREE CXB3590 COB+ Bridgelux surround 5W leds Spectrum: Full-spectrum + near infrared + Ultra Violet Driver: Taiwan Meanwell LED Drivers, Wide AC100-265V, PF>0.95 Waterproof Grade: IP44 Optics: 90 degree optical lens direct light downward to magnify par and increase canopy penetration up to 200%. Lamp Control: Gardening timing + Dimmer+ 2 ON/OFF Switch Warranty: Design lifespan > 50,000Hrs,5 years warranty available. Recommended hanging height: Veg: 24", Flower: 18"-24" Coverage: Flower @ 18"-24": 3' x 4', Veg @ 24": 4' x 4' **■ BENEFITS** Yield: Up to 0.68 pounds per light/Up to 1.5 Grams per watt Using the latest lighting technology including the USA made CREE CXB3590COB and Bridgelux 5W leds which are both specifically Environment: OperationTemperature: -10 °C~45 °C designed for horticultural lighting. Storage Temp.: 0°C~40°C Unique secondary lenses adopted to guarantee an outstanding PAR Certificated: CE, TUV, RoHS, CB, SAA, FCC, ETL output and lighting performance. 6 channels gardening timing system---built-in timer, 10/12/14/16/18/24 **SPECIFICATIONS** hours for selection Two high precision dimmers to easily control the lighting intensity and Model NO: MF-GPC03 meet the different light requirements needed by plants at each growth Carefully selected spectra delivering the sun spectrum that is needed Power: 280W by plants. **Product** Dimension: 850\*190\*70mm Daisy chain included.( 3 units MAX) Packing: 950\*280\*200mm/1pcs/carton Spectrum & PAR READINGS Weight: N.W: 8.0KG, G.W: 9.5KG CH1: COB-ON CH2:Surround LEDs-ON CH1&CH2 Full Power ON AC100-265Vac, 50-60Hz Input: >0.95 **Driver** PF. Meanwell Brand: Spectrum Full Spectrum+UV+IR **CREE+ BRIDGELUX** Brand: In 1972, McCree defined his "action spectrum" which is commonly used as a reference spectrum for photosynthesis. **LEDS** 3PCS \* 54 watt CREE CXB 3590 COB Alien LED's Spectrum perfectly match the McCREEs ACTION SPECTRUM which has been proved to be the best spectrum for a grow light. LEDS 54W/module Details: 48PCS\* 5W Bridgelux surround LEDS 40W/Module Metal PCB(Aluminum)2.0mm PCB: **Heat management** Height:50CM Height:100CM Heat conduction: 2.0w/m.k Storage Temp.: 0℃~40℃ **Environment** Operation Temp.: -10°C~45°C Gardening timing+Dimmer+2 ON/OFF switches(CH1-COB **Lamp Control** Veg & Bloom light, CH2- Bloom Enhancer light) 60° Dual core Bridgelux/ 90° for CREE COB **Optics**



E-mail: mf@mingfeng-lighting.com Websit www.mingfeng-lighting.com